

S400-M4CB2-T Hinge Safety Switch



Basic data

Series S400

Functions

Functions

Locking device without guard interlocking according to ISO 14119, Integration in control circuits up to category 4 in accordance with EN ISO 13849, Mechanical hinge with integrated safety switch

Characteristic parameters

Mission time 20 years, EN ISO 13849-1

B10_d 2,000,000 number of cycles

Electrical data

Usage category at DC 13 Ue 24 V, Ie 2 A, EN 60947-5-1

Usage category at AC 15 Ue 24 V, Ie 2 A, EN 60947-5-1

Contact allocation 2NC + 1NO

Contact opening Force-fit

Short circuit protected 500 V, 2 A, type gG, IEC 60269-1

Technical Data

Rated insulation voltage	30 V AC, 36 V DC
--------------------------	------------------

Conventional thermal current, max.	2 A
------------------------------------	-----

Connection

Number of connections	1 Piece(s)
-----------------------	------------

Connection 1

Type of connection	Cable
--------------------	-------

Function	Contact connection
----------	--------------------

Cable length	2,000 mm
--------------	----------

Sheathing material	PVC
--------------------	-----

Number of conductors	7 -wire
----------------------	---------

Mechanical data

Design	Cubic
--------	-------

Dimension (W x H x L)	49 mm x 22.5 mm x 100.6 mm
-----------------------	----------------------------

Housing material	Metal, ZAMAK
------------------	--------------

Electrical contact material	Silver alloy
-----------------------------	--------------

Net weight	481 g
------------	-------

Housing color	Silver
---------------	--------

Type of fastening	Mounting thread, Mounting plate
-------------------	---------------------------------

Side of cable entry	From above (with left installation)
---------------------	-------------------------------------

Switch type	Interlock device without guard interlocking, ISO 14119
-------------	--

Switching principle	Slow-action contact
---------------------	---------------------

Axial stress	1,500 N·m
--------------	-----------

Radial stress	1,000 N·m
---------------	-----------

Torsional stress	25 N·m
------------------	--------

Mechanical life time	1,000,000 actuation cycles, IEC 6047-5-1
----------------------	--

See more at celltec.com.au

Actuation frequency, max.	1,200 per hour, IEC 6047-5-1
Internal actuator	Safety switch in hinge, encapsulated
Actuating path (angle) with forced separation	4 N, From set switching point
Actuation angle, max.	180 °

Environmental data	
Ambient temperature, operation	-25 ... 80 °C
Degree of contamination	3, EN 60947-1

Certifications	
Degree of protection	IP 67, IP 69K

CellTec Pty Ltd

P: +61 3 8360 8533 | **E:** sales@celltec.com.au

A: 6 Paraweena Drive
Truganina VIC 3029 Australia

CellTec
engineering automation safety