SIEMENS

Data sheet

6ED1055-4MH08-0BA0

*** spare part *** LOGO! TD text display, 6-line, 3 background colors, 2 Ethernet ports, installation accessories for LOGO! 8



Figure similar

General information		
Product type designation	TD	
Suitability for use	Can be used with LOGO! 8 and higher	
Display		
Design of display	FSTN	
Line display		
Number of lines	6	
 Number of characters per line 	20	
Backlighting		
 Type of backlighting 	LED	
Control elements		
Keyboard fonts		
System keys	Yes	
 — Number of configurable system keys 	0	
 alphanumeric keyboard 	No	
Installation type/mounting		
Wall mounting/direct mounting	No	
Supply voltage		
Type of supply voltage	AC/DC	
Rated value (DC)	12 V; 12/24 V DC, 24 V AC	
Power loss		
Power loss, typ.	1.8 W; At 24 V DC	
Interrupts/diagnostics/status information		
Diagnostics function	No	
Standards, approvals, certificates		
CE mark	Yes	
UL approval	Yes	
FM approval	Yes	
KC approval	Yes	
Marine approval		
 American Bureau of Shipping (ABS) 	Yes	
Ambient conditions		
Ambient temperature during operation		
• min.	-20 °C; No condensation	
• max.	55 °C	
Ambient temperature during storage/transportation		

• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
 Ambient air temperature-barometric pressure- altitude 	Tmin Tmax at 1 080 hPa 795 hPa (-1 000 m +2 000 m)
Configuration	
Configuration software	
Configuration tool	LOGO! Soft Comfort V8
Mechanics/material	
Design of housing	plastic
Dimensions	
Width	128.2 mm
Height	86 mm
Depth	38.7 mm
Overall depth	38.7 mm
Weights	
Weight, approx.	220 g
Scope of supply	
Delivery quantity in pieces	1
	~ 1

last modified:

2/12/2021 🖸