

6ES7214-1BG40-0XB0

CPU 1214C, AC/DC/Relay, 14DI/10DO/2AI

Technical data



SIMATIC S7-1200, CPU 1214C, compact CPU, AC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 100 KB

| General information | |
|--|---|
| Product type designation | CPU 1214C AC/DC/relay |
| Firmware version | V4.4 |
| Engineering with | <ul style="list-style-type: none"> Programming package |
| | STEP 7 V16 or higher |
| Supply voltage | |
| Rated value (AC) | |
| <ul style="list-style-type: none"> 120 V AC 230 V AC | <ul style="list-style-type: none"> Yes Yes |
| permissible range, lower limit (AC) | 85 V |
| permissible range, upper limit (AC) | 264 V |
| Line frequency | |
| <ul style="list-style-type: none"> permissible range, lower limit permissible range, upper limit | <ul style="list-style-type: none"> 47 Hz 63 Hz |
| Input current | |
| Current consumption, max. | 300 mA at 120 V AC; 150 mA at 240 V AC |
| Inrush current, max. | 20 A; at 264 V |
| I ² t | 0.8 A ² ·s |
| Output current | |
| for backplane bus (5 V DC), max. | 1 600 mA; Max. 5 V DC for SM and CM |
| Encoder supply | |
| 24 V encoder supply | |
| <ul style="list-style-type: none"> 24 V | 20.4 to 28.8V |
| Power loss | |
| Power loss, typ. | 14 W |
| Memory | |
| Work memory | |
| <ul style="list-style-type: none"> integrated expandable | <ul style="list-style-type: none"> 100 kbyte No |
| Load memory | |
| <ul style="list-style-type: none"> integrated Plug-in (SIMATIC Memory Card), max. | <ul style="list-style-type: none"> 4 Mbyte with SIMATIC memory card |
| Backup | |
| <ul style="list-style-type: none"> present maintenance-free without battery | <ul style="list-style-type: none"> Yes Yes Yes |
| CPU processing times | |
| for bit operations, typ. | 0.08 µs; / instruction |
| for word operations, typ. | 1.7 µs; / instruction |
| for floating point arithmetic, typ. | 2.3 µs; / instruction |
| CPU-blocks | |
| Number of blocks (total) | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB | |
| <ul style="list-style-type: none"> Number, max. | Limited only by RAM for code |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 10 kbyte |
| Flag | |
| <ul style="list-style-type: none"> Number, max. | 8 kbyte; Size of bit memory address area |
| Local data | |
| <ul style="list-style-type: none"> per priority class, max. | 16 kbyte |
| Address area | |
| Process image | |
| <ul style="list-style-type: none"> Inputs, adjustable | 1 kbyte |

| | |
|--|--|
| • Outputs, adjustable | 1 kbyte |
| Hardware configuration | |
| Number of modules per system, max. | 3 comm. modules, 1 signal board, 8 signal modules |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • Backup time | 480 h; Typical |
| Digital inputs | |
| Number of digital inputs | 14; Integrated |
| • of which inputs usable for technological functions | 6; HSC (High Speed Counting) |
| Source/sink input | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 14 |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | 5 V DC at 1 mA |
| • for signal "1" | 15 V DC at 2.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |
| — at "0" to "1", min. | 0.2 ms |
| — at "0" to "1", max. | 12.8 ms |
| for interrupt inputs | |
| — parameterizable | Yes |
| for technological functions | |
| — parameterizable | Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz |
| Cable length | |
| • shielded, max. | 500 m; 50 m for technological functions |
| • unshielded, max. | 300 m; for technological functions: No |
| Digital outputs | |
| Number of digital outputs | 10; Relays |
| Switching capacity of the outputs | |
| • with resistive load, max. | 2 A |
| • on lamp load, max. | 30 W with DC, 200 W with AC |
| Output delay with resistive load | |
| • "0" to "1", max. | 10 ms; max. |
| • "1" to "0", max. | 10 ms; max. |
| Relay outputs | |
| • Number of relay outputs | 10 |
| • Number of operating cycles, max. | mechanically 10 million, at rated load voltage 100 000 |
| Cable length | |
| • shielded, max. | 500 m |
| • unshielded, max. | 150 m |
| Analog inputs | |
| Number of analog inputs | 2 |
| Input ranges | |
| • Voltage | Yes |
| Input ranges (rated values), voltages | |
| • 0 to +10 V | Yes |
| — Input resistance (0 to 10 V) | ≥100k ohms |
| Cable length | |
| • shielded, max. | 100 m; twisted and shielded |
| Analog outputs | |
| Number of analog outputs | 0 |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| • Resolution with overrange (bit including sign), max. | 10 bit |
| • Integration time, parameterizable | Yes |
| • Conversion time (per channel) | 625 μs |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| 1. Interface | |
| Isolated | Yes |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| • RJ 45 (Ethernet) | Yes |
| • Number of ports | 1 |
| • integrated switch | No |
| Protocols | |
| • PROFINET IO Controller | Yes |
| • PROFINET IO Device | Yes |
| • SIMATIC communication | Yes |

| | |
|---|---|
| <ul style="list-style-type: none"> • Open IE communication | Yes; Optionally also encrypted |
| <ul style="list-style-type: none"> • Web server | Yes |
| <ul style="list-style-type: none"> • Media redundancy | No |
| PROFINET IO Controller | |
| <ul style="list-style-type: none"> • Transmission rate, max. | 100 Mbit/s |
| Services | |
| <ul style="list-style-type: none"> — PG/OP communication | Yes |
| <ul style="list-style-type: none"> — Isochronous mode | No |
| <ul style="list-style-type: none"> — IRT | No |
| <ul style="list-style-type: none"> — PROFinergy | No |
| <ul style="list-style-type: none"> — Prioritized startup | Yes |
| <ul style="list-style-type: none"> — Number of IO devices with prioritized startup, max. | 16 |
| <ul style="list-style-type: none"> — Number of connectable IO Devices, max. | 16 |
| <ul style="list-style-type: none"> — Number of connectable IO Devices for RT, max. | 16 |
| <ul style="list-style-type: none"> — of which in line, max. | 16 |
| <ul style="list-style-type: none"> — Activation/deactivation of IO Devices | Yes |
| <ul style="list-style-type: none"> — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8 |
| <ul style="list-style-type: none"> — Updating time | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |
| PROFINET IO Device | |
| Services | |
| <ul style="list-style-type: none"> — PG/OP communication | Yes |
| <ul style="list-style-type: none"> — Isochronous mode | No |
| <ul style="list-style-type: none"> — IRT | No |
| <ul style="list-style-type: none"> — PROFinergy | Yes |
| <ul style="list-style-type: none"> — Shared device | Yes |
| <ul style="list-style-type: none"> — Number of IO Controllers with shared device, max. | 2 |
| Protocols | |
| Supports protocol for PROFINET IO | Yes |
| PROFIBUS | Yes; CM 1243-5 (master) or CM 1242-5 (slave) required |
| AS-Interface | Yes; CM 1243-2 required |
| Protocols (Ethernet) | |
| <ul style="list-style-type: none"> • TCP/IP | Yes |
| <ul style="list-style-type: none"> • DHCP | No |
| <ul style="list-style-type: none"> • SNMP | Yes |
| <ul style="list-style-type: none"> • DCP | Yes |
| <ul style="list-style-type: none"> • LLDP | Yes |
| Redundancy mode | |
| Media redundancy | |
| <ul style="list-style-type: none"> — MRP | No |
| <ul style="list-style-type: none"> — MRPD | No |
| SIMATIC communication | |
| <ul style="list-style-type: none"> • S7 routing | Yes |
| Open IE communication | |
| <ul style="list-style-type: none"> • TCP/IP | Yes |
| <ul style="list-style-type: none"> — Data length, max. | 8 kbyte |
| <ul style="list-style-type: none"> • ISO-on-TCP (RFC1006) | Yes |
| <ul style="list-style-type: none"> — Data length, max. | 8 kbyte |
| <ul style="list-style-type: none"> • UDP | Yes |
| <ul style="list-style-type: none"> — Data length, max. | 1 472 byte |
| Web server | |
| <ul style="list-style-type: none"> • supported | Yes |
| <ul style="list-style-type: none"> • User-defined websites | Yes |
| OPC UA | |
| <ul style="list-style-type: none"> • Runtime license required | Yes |
| <ul style="list-style-type: none"> • OPC UA Server | Yes; Data access (read, write, subscribe), runtime license required |
| <ul style="list-style-type: none"> — Number of sessions, max. | 5 |
| <ul style="list-style-type: none"> — Number of accessible variables, max. | 1 000 |
| <ul style="list-style-type: none"> — Number of subscriptions per session, max. | 5 |
| <ul style="list-style-type: none"> — Sampling interval, min. | 100 ms |
| <ul style="list-style-type: none"> — Publishing interval, min. | 200 ms |
| <ul style="list-style-type: none"> — Number of monitored items, max. | 500 |
| <ul style="list-style-type: none"> — Number of server interfaces, max. | 2 |
| <ul style="list-style-type: none"> — Number of nodes for user-defined server interfaces, max. | 1 000 |
| Further protocols | |
| <ul style="list-style-type: none"> • MODBUS | Yes |
| Communication functions | |
| S7 communication | |
| <ul style="list-style-type: none"> • supported | Yes |
| <ul style="list-style-type: none"> • as server | Yes |
| <ul style="list-style-type: none"> • as client | Yes |
| <ul style="list-style-type: none"> • User data per job, max. | See online help (S7 communication, user data size) |
| Number of connections | |
| <ul style="list-style-type: none"> • overall | 16; dynamically |
| Test commissioning functions | |
| Status/control | |

| | |
|--|---|
| • Status/control variable | Yes |
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing | |
| • Forcing | Yes |
| Diagnostic buffer | |
| • present | Yes |
| Traces | |
| • Number of configurable Traces | 2 |
| • Memory size per trace, max. | 512 kbyte |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| • RUN/STOP LED | Yes |
| • ERROR LED | Yes |
| • MAINT LED | Yes |
| Integrated Functions | |
| Number of counters | 6 |
| Counting frequency (counter) max. | 100 kHz |
| Frequency measurement | Yes |
| controlled positioning | Yes |
| Number of position-controlled positioning axes, max. | 8 |
| Number of positioning axes via pulse-direction interface | Up to 4 with SB 1222 |
| PID controller | Yes |
| Number of alarm inputs | 4 |
| Potential separation | |
| Potential separation digital inputs | |
| • Potential separation digital inputs | 500V AC for 1 minute |
| • between the channels, in groups of | 1 |
| Potential separation digital outputs | |
| • Potential separation digital outputs | Relays |
| • between the channels | No |
| • between the channels, in groups of | 2 |
| EMC | |
| Interference immunity against discharge of static electricity | |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes |
| — Test voltage at air discharge | 8 kV |
| — Test voltage at contact discharge | 6 kV |
| Interference immunity to cable-borne interference | |
| • Interference immunity on supply lines acc. to IEC 61000-4-4 | Yes |
| • Interference immunity on signal cables acc. to IEC 61000-4-4 | Yes |
| Interference immunity against voltage surge | |
| • Interference immunity on supply lines acc. to IEC 61000-4-5 | Yes |
| Interference immunity against conducted variable disturbance induced by high-frequency fields | |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class A, for use in industrial areas | Yes; Group 1 |
| • Limit class B, for use in residential areas | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |
| Standards, approvals, certificates | |
| CE mark | Yes |
| UL approval | Yes |
| cULus | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| Marine approval | Yes |
| Ambient conditions | |
| Free fall | |
| • Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
| • min. | -20 °C |
| • max. | 60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical |
| • horizontal installation, min. | -20 °C |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | -20 °C |
| • vertical installation, max. | 50 °C |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| • Operation, min. | 795 hPa |
| • Operation, max. | 1 080 hPa |
| • Storage/transport, min. | 660 hPa |
| • Storage/transport, max. | 1 080 hPa |
| Altitude during operation relating to sea level | |

| | |
|---|---|
| • Installation altitude, min. | -1 000 m |
| • Installation altitude, max. | 2 000 m |
| Relative humidity | |
| • Operation, max. | 95 %; no condensation |
| Vibrations | |
| • Vibration resistance during operation acc. to IEC 60068-2-6 | 2 g (m/s ²) wall mounting, 1 g (m/s ²) DIN rail |
| • Operation, tested according to IEC 60068-2-6 | Yes |
| Shock testing | |
| • tested according to IEC 60068-2-27 | Yes |
| Configuration | |
| Programming | |
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — SCL | Yes |
| Know-how protection | |
| • User program protection/password protection | Yes |
| • Copy protection | Yes |
| • Block protection | Yes |
| Access protection | |
| • Protection level: Write protection | Yes |
| • Protection level: Read/write protection | Yes |
| • Protection level: Complete protection | Yes |
| Cycle time monitoring | |
| • adjustable | Yes |
| Dimensions | |
| Width | 110 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weights | |
| Weight, approx. | 455 g |
| last modified: | 2/5/2021 |

Last changes: 02/09/2021